

### Overview

## HP 3100 SI Switch Series

### Models

HP 3100-8 v2 SI Switch	JG221A
HP 3100-16 v2 SI Switch	JG222A
HP 3100-24 v2 SI Switch	JG223A

### Key features

- Suitable for enterprise networks and MANs
- 8, 16, 24 x 10/100 downlink ports
- Gigabit Ethernet uplinks
- Link aggregation
- Small size with noise-free design

### Product overview

The HP 3100 SI Switch Series is a low-cost Fast Ethernet switch line that enables organizations to do more with less. Stackable and affordable, this series comprises intelligent, network-manageable Layer 2 Fast Ethernet switches that offer high performance, high port density, and easy installation. These switches provide 10/100 Mbps downlinks and Gigabit Ethernet uplinks, and offer link aggregation that expands bandwidth and enhances connection reliability. In enterprise networks, they can serve as access devices for 100 Mbps-to-desktop applications. In metropolitan area networks (MANs) or industry networks, they can connect end users or aggregate low-end switches through 100 Mbps electrical interfaces in the downlink direction, converging at an IP switching center or a large-capacity Layer 3 switch in the uplink direction via a GbE interface or link aggregation.

### Features and benefits

#### Quality of Service (QoS)

- **Powerful QoS feature**  
supports the following congestion actions: weighted round robin queuing and HQ+WRR
- **Broadcast control**  
allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

#### Management

- **Friendly port names**  
allow assignment of descriptive names to ports
- **Remote configuration and management**  
is available through a secure Web browser or a CLI
- **Manager and operator privilege levels**  
enable read-only (operator) and read/write (manager) access on CLI and Web browser management interfaces
- **Command authorization**  
leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; an audit trail documents activity
- **Secure Web GUI**  
provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Multiple configuration files**  
can be stored to the flash image
- **Complete session logging**  
provides detailed information for problem identification and resolution
- **SNMPv1, v2c, and v3**  
facilitate centralized discovery, monitoring, and secure management of networking devices

### Overview

- **Remote monitoring (RMON)**  
uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **Management VLAN**  
segments traffic to and from management interfaces, including CLI/telnet, a Web browser interface, and SNMP
- **Troubleshooting**  
ingress and egress port monitoring enable network problem solving; virtual cable tests provide visibility into cable problems
- **Stacking capability**  
single IP address management for a stack of up to 16 switches

### Connectivity

- **Auto-MDIX**  
automatically adjusts for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **Flow control**  
provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations
- **Gigabit Ethernet uplinks**  
are dual-personality ports for either 10/100/1000 or mini-GBIC SFP connectivity for increased connectivity flexibility

### Performance

- **Gigabit Ethernet interface**  
provides a connection to the network that eliminates the network as a bottleneck

### Resiliency and high availability

- **Separate data and control paths**  
increase security and performance
- **Spanning Tree/MSTP, RSTP**  
provides redundant links while preventing network loops
- **Port trunking**  
provides higher switch-to-switch throughput and link-level redundancy, with support for standards-based link aggregation (IEEE 802.3ad)

### Layer 2 switching

- **8K MAC addresses**  
provide access to many Layer 2 devices
- **VLAN support and tagging**  
support IEEE 802.1Q with 4,094 simultaneous VLAN IDs
- **GARP VLAN Registration Protocol**  
allows automatic learning and dynamic assignment of VLANs
- **Gigabit Ethernet port aggregation**  
allows grouping of ports to increase overall data throughput to a remote device
- **IEEE 802.1ad QinQ**  
increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network

### Overview

#### Security

- **IEEE 802.1X**  
industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
- **MAC-based authentication**  
client is authenticated with the RADIUS server based on the client's MAC address
- **Secure management access**  
securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Secure FTP**  
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Guest VLAN**  
similar to IEEE 802.1X, it provides a browser-based environment to authenticated clients
- **Port security**  
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **Port isolation**  
secures and adds privacy, and prevents malicious attackers from obtaining user information
- **STP BPDU port protection**  
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP Root Guard**  
protects the root bridge from malicious attacks or configuration mistakes
- **RADIUS/HWTACACS**  
eases switch management security administration by using a password authentication server
- **HTTPS management**  
provides secure Web management

#### Convergence

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
is an automated device discovery protocol that provides easy mapping of network management applications
- **LLDP-MED**  
is a standard extension that automatically configures network devices, including LLDP-capable IP phones
- **IP multicast snooping (data-driven IGMP)**  
automatically prevents flooding of IP multicast traffic
- **Multicast VLAN**  
allows multiple VLANs to receive the same multicast traffic, reducing network bandwidth demand by eliminating multiple streams to each VLAN

#### Flexibility

- **Fanless design**  
enables quiet operation for deployment in open spaces (selected models)

#### Additional information

- **Green initiative support**  
provides support for RoHS and WEEE regulations
- **Green IT and power**  
uses the latest advances in silicon development and shuts off unused ports to improve power efficiency

#### Warranty and support

### Overview

- **Limited Lifetime Warranty v2.0**  
advance hardware replacement with next-business-day delivery (available in most countries). See [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary) for duration details.
- **Electronic and telephone support (for Limited Lifetime Warranty 2.0)**  
limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases**  
to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

Tel: 051-891-2000  
www.2000info.co.kr

### Technical Specifications

#### HP 3100-8 v2 SI Switch (JG221A)

<b>Ports</b>	1 dual-personality 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 8 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 1 RJ-45 serial console port	
<b>Physical characteristics</b>	<b>Dimensions</b>	9.06(w) x 6.3(d) x 1.72(h) in (23.01 x 16 x 4.37 cm) (1U height)
	<b>Weight</b>	6.61 lb (3 kg)
<b>Memory and processor</b>	128 MB SDRAM, 16 MB flash; packet buffer size: 384 KB	
<b>Mounting</b>	Requires angle mounting set if rack mounted (not included)	
<b>Performance</b>	<b>100 Mb Latency</b>	< 6 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	up to 2.7 million pps
	<b>Routing/Switching capacity</b>	3.6 Gbps
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	10% to 90%, non-condensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	5% to 95%, non-condensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	31 BTU/hr (32.71 kJ/hr)
	<b>Voltage</b>	100-240 VAC
	<b>Maximum power rating</b>	9 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
<b>Management Services</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager 3-year, 4-hour onsite, 13x5 coverage for hardware (UV810E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UV813E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV816E) 3-year, 24x7 SW phone support, software updates (UV819E) Installation with minimum configuration, system-based pricing (UX114E) Installation with HP-provided configuration, system-based pricing (UX115E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV811E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UV814E)	

### Technical Specifications

- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV817E)
- 4-year, 24x7 SW phone support, software updates (UV820E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV812E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UV815E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV818E)
- 5-year, 24x7 SW phone support, software updates (UV821E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW428E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW429E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW430E)
- 1-year, 4-hour onsite, 13x5 coverage for hardware (HR594E)
- 1-year, 4-hour onsite, 24x7 coverage for hardware (HR595E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR598E)
- 1-year, 24x7 software phone support, software updates (HR597E)
- 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR596E)
- 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS698E)
- 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS699E)
- 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS700E)
- 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS701E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS702E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS703E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS704E)
- 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS705E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP 3100-16 v2 SI Switch (JG222A)

<b>Ports</b>	2 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 16 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 1 RJ-45 serial console port	
<b>Physical characteristics</b>	<b>Dimensions</b>	14.17(w) x 6.3(d) x 1.72(h) in (35.99 x 16 x 4.37 cm) (1U height)
	<b>Weight</b>	6.61 lb (3 kg)
<b>Memory and processor</b>	128 MB SDRAM, 16 MB flash; packet buffer size: 384 KB	
<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
<b>Performance</b>	<b>100 Mb Latency</b>	< 6 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	5.4 million pps
	<b>Routing/Switching capacity</b>	7.2 Gbps
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	10% to 90%, non-condensing
	<b>Non-operating/Storage</b>	-40°F to 158°F (-40°C to 70°C)

### Technical Specifications

	<b>temperature</b>	
	<b>Non-operating/Storage relative humidity</b>	5% to 95%, non-condensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	41 BTU/hr (43.26 kJ/hr)
	<b>Voltage</b>	100-240 VAC
	<b>Maximum power rating</b>	12 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
<b>Management Services</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager	
	3-year, 4-hour onsite, 13x5 coverage for hardware (UV810E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (UV813E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV816E)	
	3-year, 24x7 SW phone support, software updates (UV819E)	
	Installation with minimum configuration, system-based pricing (UX114E)	
	Installation with HP-provided configuration, system-based pricing (UX115E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (UV811E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (UV814E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV817E)	
	4-year, 24x7 SW phone support, software updates (UV820E)	
	5-year, 4-hour onsite, 13x5 coverage for hardware (UV812E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware (UV815E)	
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV818E)	
	5-year, 24x7 SW phone support, software updates (UV821E)	
	3 Yr 6 hr Call-to-Repair Onsite (UW428E)	
	4 Yr 6 hr Call-to-Repair Onsite (UW429E)	
	5 Yr 6 hr Call-to-Repair Onsite (UW430E)	
	1-year, 4-hour onsite, 13x5 coverage for hardware (HR594E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware (HR595E)	
	1-year, 6 hour Call-To-Repair Onsite for hardware (HR598E)	
	1-year, 24x7 software phone support, software updates (HR597E)	
	1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR596E)	
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS698E)	
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS699E)	
	3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS700E)	
	3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS701E)	
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS702E)	
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS703E)	
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange	



### Technical Specifications

(HS704E)

5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS705E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP 3100-24 v2 SI Switch (JG223A)

<b>Ports</b>	2 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 24 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 1 RJ-45 serial console port	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.32(w) x 6.3(d) x 1.72(h) in (43.99 x 16 x 4.37 cm) (1U height)
	<b>Weight</b>	6.61 lb (3 kg)
<b>Memory and processor</b>	128 MB SDRAM, 16 MB flash; packet buffer size: 384 KB	
<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
<b>Performance</b>	<b>100 Mb Latency</b>	< 6 $\mu$ s
	<b>1000 Mb Latency</b>	< 5 $\mu$ s
	<b>Throughput</b>	6.6 million pps
	<b>Routing/Switching capacity</b>	8.8 Gbps
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	10% to 90%, non-condensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	5% to 95%, non-condensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	44 BTU/hr (46.42 kJ/hr)
	<b>Voltage</b>	100-240 VAC
	<b>Maximum power rating</b>	13 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11; FDA 21 CFR Subchapter J; ROHS Compliance	
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
<b>Management Services</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager 3-year, 4-hour onsite, 13x5 coverage for hardware (UV810E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UV813E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV816E)	



### Technical Specifications

3-year, 24x7 SW phone support, software updates (UV819E)  
Installation with minimum configuration, system-based pricing (UX114E)  
Installation with HP-provided configuration, system-based pricing (UX115E)  
4-year, 4-hour onsite, 13x5 coverage for hardware (UV811E)  
4-year, 4-hour onsite, 24x7 coverage for hardware (UV814E)  
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV817E)  
4-year, 24x7 SW phone support, software updates (UV820E)  
5-year, 4-hour onsite, 13x5 coverage for hardware (UV812E)  
5-year, 4-hour onsite, 24x7 coverage for hardware (UV815E)  
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV818E)  
5-year, 24x7 SW phone support, software updates (UV821E)  
3 Yr 6 hr Call-to-Repair Onsite (UW428E)  
4 Yr 6 hr Call-to-Repair Onsite (UW429E)  
5 Yr 6 hr Call-to-Repair Onsite (UW430E)  
1-year, 4-hour onsite, 13x5 coverage for hardware (HR594E)  
1-year, 4-hour onsite, 24x7 coverage for hardware (HR595E)  
1-year, 6 hour Call-To-Repair Onsite for hardware (HR598E)  
1-year, 24x7 software phone support, software updates (HR597E)  
1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR596E)  
1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS698E)  
1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS699E)  
3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS700E)  
3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS701E)  
4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS702E)  
4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS703E)  
5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS704E)  
5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS705E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### Standards and protocols

(applies to all products in series)

#### General protocols

IEEE 802.1D MAC Bridges  
IEEE 802.1p Priority  
IEEE 802.1Q VLANs  
IEEE 802.1s Multiple Spanning Trees  
IEEE 802.1w Rapid Reconfiguration of Spanning Tree  
IEEE 802.3ab 100BASE-T  
IEEE 802.3ad Link Aggregation Control Protocol (LACP)  
IEEE 802.3i 10BASE-T  
IEEE 802.3u 100BASE-X  
IEEE 802.3x Flow Control  
IEEE 802.3z 1000BASE-X  
RFC 768 UDP  
RFC 791 IP  
RFC 792 ICMP  
RFC 793 TCP  
RFC 826 ARP  
RFC 854 TELNET  
RFC 951 BOOTP

### Technical Specifications

#### **MIBs**

IEEE 8021-PAE-MIB  
IEEE 8023-LAG-MIB  
RFC 1213 MIB II  
RFC 1493 Bridge MIB  
RFC 2011 SNMPv2 MIB for IP  
RFC 2013 SNMPv2 MIB for UDP  
RFC 2233 Interface MIB  
RFC 2571 SNMP Framework MIB  
RFC 2572 SNMP-MPD MIB  
RFC 2573 SNMP-Notification MIB  
RFC 2573 SNMP-Target MIB  
RFC 2618 RADIUS Authentication Client MIB  
RFC 2620 RADIUS Accounting Client MIB  
RFC 2665 Ethernet-Like-MIB  
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB  
RFC 2819 RMON MIB  
RFC 2925 Ping MIB  
RFC 3414 SNMP-User based-SM MIB  
RFC 3415 SNMP-View based-ACM MIB  
RFC 3418 MIB for SNMPv3  
RFC 3826 AES for SNMP's USM MIB  
RFC 4113 UDP MIB  
LLDP-EXT-DOT1-MIB  
LLDP-EXT-DOT3-MIB  
LLDP-MIB

#### **Network management**

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)  
RFC 1157 SNMPv1  
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)  
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)  
SNMPv1/v2c/v3

### Accessory Product Details

<b>HP 3100 SI Switch Series accessories</b>	<b>Modules</b>	
	HP 1 Port Gig-T 3100 SI Module	JD298A
	HP 1 Port Gig-LX SC 3100 SI Module	JD299A
	HP 1 Port Gig-SX SC 3100 SI Module	JD300A
	HP 1-Port 10/100Base-T POE 3100 SI Module	JD301A
	<b>HP 3100-8 v2 SI Switch (JG221A)</b>	
	HP 3100/4210-9 Rack Mount Kit	JD322A
	<b>HP 3100-16 v2 SI Switch (JG222A)</b>	
	HP 3100/4210-16 Rack Mount Kit	JD321A

Tel: 051-891-2000  
www.2000info.co.kr

### Summary of Changes

Date	Version History	Action	Description of Change:
01-Dec-2014	From Version 6 to 7	Changed	Warranty and support updated
05-Oct-2012	From Version 5 to 6	Changed	Features and benefits was revised as were the listing of models (removed 3), and the weight and dimensions in each model specification.
15-Mar-2012	From Version 4 to 5	Changed	Features and benefits was revised and new Models and Accessories were added.
07-Nov-2011	From Version 3 to 4	Changed	The product name was updated throughout the document.
15-Apr-2011	From Version 2 to 3	Removed	Removed the remaining mentions of ProCurve from the QS.
07-Mar-2011	From Version 1 to 2	Changed	Accessories product descriptions and notes and services in Models were revised.

To learn more, visit [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2010-2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of Microsoft Corporation.